

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
REQUEST FOR FILING NATIONAL PHASE OF
PCT APPLICATION UNDER 35 U.S.C. 371 AND 37 CFR 1.494 OR 1.495To: Hon. Commissioner of Patents
Washington, D.C. 20231

00909

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)Atty Dkt: PM 277084 ✓ /2980337US/HS/her
M# /Client Ref.

From: Pillsbury Winthrop LLP, IP Group:

Date: February 14, 2001This is a **REQUEST** for **FILING** a PCT/USA National Phase Application based on:

1. International Application	2. International Filing Date	3. Earliest Priority Date Claimed
<u>PCT/FI99/00676</u> ✓	<u>16</u> <u>August</u> <u>1999</u> ✓	<u>18</u> <u>August</u> <u>1998</u> ✓
↑ country code	Day MONTH Year	Day MONTH Year
		(use item 2 if no earlier priority)

4. Measured from the earliest priority date in item 3, this PCT/USA National Phase Application Request is being filed within:

(a) ☐ 20 months from above item 3 date (b) ☒ 30 months from above item 3 date,(c) Therefore, the due date (unextendable) is February 18, 2001Title of Invention TRACING OF SIGNALLING MESSAGESInventor(s) EINAMO, Kari ✓

Applicant herewith submits the following under 35 U.S.C. 371 to effect filing:

☒ Please immediately start national examination procedures (35 U.S.C. 371 (f)).☐ A copy of the International Application as filed (35 U.S.C. 371(c)(2)) is transmitted herewith (file if in English but, if in foreign language, file only if not transmitted to PTO by the International Bureau) including:a. ☐ Request;b. ☐ Abstract;c. pgs. Spec. and Claims;d. sheet(s) Drawing which are ☐ informal ☐ formal of size ☐ A4 ☐ 11"9. ☒ A copy of the International Application has been transmitted by the International Bureau.

10. A translation of the International Application into English (35 U.S.C. 371(c)(2))

a. ☒ is transmitted herewith including: (1) ☒ Request; (2) ☒ Abstract;(3) 16 pgs. Spec. and Claims;(4) 2 sheet(s) Drawing which are:☐ informal ☒ formal of size ☒ A4 ☐ 11"b. ☐ is not required, as the application was filed in English.c. ☐ is not herewith, but will be filed when required by the forthcoming PTO Missing Requirements Notice per Rule 494(c) if box 4(a) is X'd or Rule 495(c) if box 4(b) is X'd.d. ☐ Translation verification attached (not required now).

11. ☒ **PLEASE AMEND** the specification before its first line by inserting as a separate paragraph:
a. ☒ --This application is the national phase of international application PCT/FI99/00676
filed August 16, 1999 which designated the U.S.--
b. ☐ --This application also claims the benefit of U.S. Provisional Application No.
60/_____, filed _____.
12. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)), i.e., **before 18th month from first priority date above in item 3, are transmitted herewith (file only if in English) including:**
13. ☒ PCT Article 19 claim amendments (if any) have been transmitted by the International Bureau
14. ☐ Translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)), i.e., of **claim amendments made before 18th month, is attached (required by 20th month from the date in item 3 if box 4(a) above is X'd, or 30th month if box 4(b) is X'd, or else amendments will be considered canceled).**
15. **A declaration of the inventor** (35 U.S.C. 371(c)(4))
a. ☒ is submitted herewith ☒ Original ☐ Facsimile/Copy
b. ☐ is not herewith, but will be filed when required by the forthcoming PTO Missing Requirements Notice per Rule 494(c) if box 4(a) is X'd or Rule 495(c) if box 4(b) is X'd.
16. **An International Search Report (ISR):**
a. Was prepared by ☐ European Patent Office ☐ Japanese Patent Office ☒ Other
b. ☒ has been transmitted by the international Bureau to PTO.
c. ☒ copy herewith (1 pg(s).) ☒ plus Annex of family members (1 pg(s).).
- International Preliminary Examination Report (IPER):**
a. ☒ has been transmitted (if this letter is filed after 28 months from date in item 3) in English by the International Bureau with Annexes (if any) in original language.
b. ☒ copy herewith in English.
c.1 ☐ IPER Annex(es) in original language ("Annexes" are amendments made to claims/spec/drawings during Examination) including attached amended:
c.2 ☐ Specification/claim pages #____ claims #
Dwg Sheets #
d. ☐ Translation of Annex(es) to IPER **(required by 30th month due date, or else annexed amendments will be considered canceled).**
- Information Disclosure Statement** including:
a. ☒ Attached Form PTO-1449 listing documents
b. ☒ Attached copies of documents listed on Form PTO-1449
c. ☒ A concise explanation of relevance of ISR references is given in the ISR.
19. ☒ **Assignment** document and Cover Sheet for recording are attached. Please mail the recorded assignment document back to the person whose signature, name and address appear at the end of this letter.
20. ☐ Copy of Power to IA agent.
21. ☐ **Drawings** (complete only if 8d or 10a(4) not completed): ____ sheet(s) per set: ☐ 1 set informal;
☐ Formal of size ☐ A4 ☐ 11"
22. Small Entity Status ☐ is **Not** claimed ☐ is claimed (**pre-filing confirmation required**)
22(a) ____ (No.) Small Entity Statement(s) enclosed (since 9/8/00 Small Entity Statements(s) not essential to make claim)
23. **Priority** is hereby claimed under 35 U.S.C. 119/365 based on the priority claim and the certified copy, both filed in the International Application during the international stage based on the filing in (country) FINLAND of:
- | | Application No. | Filing Date | | Application No. | Filing Date |
|-----|-----------------|-----------------|-----|-----------------|-------------|
| (1) | 981773 | August 18, 1998 | (2) | | |
| (3) | | | (4) | | |
| (5) | | | (6) | | |
- a. ☒ See Form PCT/IB/304 sent to US/DO with copy of priority documents. If copy has not been received, please proceed promptly to obtain same from the IB.
b. ☐ Copy of Form PCT/IB/304 attached.

24. Attached:

25. Preliminary Amendment: ATTACHED

25.5 Per Item 17.c2, **cancel original** pages #_____, claims #_____, Drawing Sheets #26. **Calculation of the U.S. National Fee (35 U.S.C. 371 (c)(1)) and other fees is as follows:**Based on amended claim(s) per above item(s) ☐ 12, ☐ 14, ☐ 17, ☒ 25, ☐ 25.5 (hilitte)

Total Effective Claims	12	minus 20 =	0	x \$18/\$9	=	\$0	966/967
Independent Claims	3	minus 3 =	0	x \$80/\$40	=	\$0	964/965
If any proper (ignore improper) Multiple Dependent claim is present,				add \$270/\$135	+	0	968/969

BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(4)): → → **BASIC FEE REQUIRED, NOW** → → → →A. If country code letters in item 1 are not "US", "BR", "BB", "TT", "MX", "IL", "NZ", "IN" or "ZA"

See item 16 re:

1. Search Report was <u>not</u> prepared by EPO or JPO -----	add \$1000/\$500		960/961
2. Search Report was prepared by EPO or JPO -----	add \$860/\$430	+1000	970/971

SKIP B, C, D AND E UNLESS country code letters in item 1 are "US", "BR", "BB", "TT", "MX", "IL", "NZ", "IN" or "ZA"

→ <input type="checkbox"/> B. If <u>USPTO</u> did not issue <u>both</u> International Search Report (ISR) <u>and</u> (if box 4(b) above is X'd) the International Examination Report (IPER), -----	add \$970/\$485	+0	960/961
→ <input type="checkbox"/> C. If <u>USPTO</u> issued ISR but not IPER (or box 4(a) above is X'd), -----	add \$710/\$355	+0	958/959
→ <input type="checkbox"/> D. If <u>USPTO</u> issued IPER but IPER Sec. V boxes <u>not all</u> 3 YES, -----	add \$690/\$345	+0	956/957
→ <input type="checkbox"/> E. If international preliminary examination fee was paid to <u>USPTO</u> and Rules 492(a)(4) and 496(b) <u>satisfied</u> (IPER Sec. V <u>all</u> 3 boxes YES for <u>all</u> claims), -----	add \$100/\$50	+0	962/963

27. **SUBTOTAL = \$1000**

28. If Assignment box 19 above is X'd, add Assignment Recording fee of ----\$40 +40 (581)

29. Attached is a check to cover the ----- **TOTAL FEES \$1040**

Our Deposit Account No. 03-3975

Our Order No. 60258 | 277084
C# M#

00909

CHARGE STATEMENT: The Commissioner is hereby authorized to charge any fee specifically authorized hereafter, or any missing or insufficient fee(s) filed, or asserted to be filed, or which should have been filed herewith or concerning any paper filed hereafter, and which may be required under Rules 16-18 and 492 (missing or insufficient fee only) now or hereafter relative to this application and the resulting Official document under Rule 20, or credit any overpayment, to our Account/Order Nos. shown above for which purpose a duplicate copy of this sheet is attached.**This CHARGE STATEMENT does not authorize charge of the issue fee until/unless an issue fee transmittal form is filed****Pillsbury Winthrop LLP
Intellectual Property Group**By Atty: Richard C. IrvingReg. No. 38499Sig: Richard C. IrvingFax: (202) 822-0944
Tel: (202) 861-3788

Atty/Sec: RCI/mhn

NOTE: File in duplicate with 2 postcard receipts (PAT-103) & attachments.

IN THE UNITED STATES PATENT OFFICE

528 Rec'd PCT/PTO 14 FEB 2001

In re PATENT APPLICATION of

EINAMO, Kari

Atty Dkt.: 277084/2980337US/HS/HER

Appln. No.:

Group Art Unit:

Filed: HEREWITH

Examiner:

Title: TRACING OF SIGNALLING MESSAGES

* * * * *

Date February 14, 2001

PRELIMINARY AMENDMENT

Hon. Commissioner of Patents
and Trademarks Office
Washington, D.C. 20231

Sir:

Please amend this application as follows:

IN THE CLAIMS:

Claim 3, line 1, delete " or 2 "

Claim 5, line 1, delete " 2 or 3,"

Claim 6, line 1, change " any one. . . claims " to - - claim 1 --

Claim 9, line 1, delete " or 8 "

Claim 12, line 1, delete " or 11 "

Respectfully submitted,

PILLSBURY WINTHROP LLP

By Richard C. Irving
Richard C. Irving
Reg. No. 38,499
Tel. No.: (202) 861-3788
Fax No.: (202) 822-0944

RCI/mhn
1100 New York Avenue, N.W.
Ninth Floor
Washington, D.C. 20005-3918
(202) 861-3000

0976922-02401
T04T29-22629260

TRACING OF SIGNALLING MESSAGES.

BACKGROUND OF THE INVENTION

The invention relates to tracing of signalling messages related to a subscriber in a mobile communication system, and particularly to tracing signalling messages of a specific subscriber.

Mobile communication systems have been developed because it has been necessary to be able to reach people even when they are not close to a fixed telephone terminal. The most important service provided by the mobile communication system is that the subscriber can make a call or he can be called, regardless of the subscriber's location in the coverage area of the system. Besides the mobile communication systems, the supplementary services provided through mobile stations have also developed. Most of these supplementary services are also available when the mobile subscriber roams from one network to another. To provide the services, the network elements or processes of the mobile communication system have to exchange information on the subscriber. This information is exchanged using signalling messages. Situations in which the subscriber cannot access the desired service or the service does not function as it should are relatively common. Causes of faults are searched for by tracing signalling messages related to the subscriber. In the pan-European mobile communication system GSM (Global System for Mobile Communications), for example, tracing is in practice carried out by taking snap shots from the signalling message flow and by analyzing their contents. A snap shot is a temporally limited sample from all signalling between the network elements or processes that are monitored.

The problem related to the arrangement described above is that as the signalling load increases, the buffers reserved for snap shots fill up rather quickly, and thus it is probable that the snap shots contain only some of the necessary messages or no necessary messages at all. Even if the signalling load were small, it would not be possible to ensure in any way that the snap shot contains the signalling messages that are to be traced. A further problem is that snap shots are usually rather large in size, and thus it takes a lot of time and effort to separate necessary messages from the unnecessary messages.

BRIEF DESCRIPTION OF THE INVENTION

An object of the invention is to provide a method and an apparatus implementing the method to eliminate the above-mentioned problems. The

objects are achieved with a method according to the invention which comprises transmitting and receiving signalling messages in a functional entity, which is an entity for subscriber mobility management in a mobile communication system, the method being characterized in that said functional entity receives a trace command which indicates the tracer and identifies at least one subscriber whose signalling messages are to be traced, and tracing is started, tracing comprising the following steps:

copying a signalling message in response to reception or transmission of the signalling message related to the subscriber to be traced, and

sending a copy to the tracer.

Here the term 'tracer' refers to the network address or memory address to which copied signalling messages are sent or in which they are stored.

The invention also relates to a system where the method of the invention can be employed. The system of the invention comprises subscribers, at least some of the subscribers being able to roam within the coverage area of the system, one or more network elements which receive and transmit signalling messages to manage subscriber mobility, and operating means for giving instructions to the network element. The system is characterized in that the operating means are arranged to give a trace command to the network element, the command indicating the tracer and identifying at least one subscriber whose signalling messages are to be traced, and the network element is arranged to copy signalling messages related to the subscriber to be traced in response to the trace command and to send a copy to the tracer.

The invention further relates to a network element which can be utilized in the method of the invention. The network element of the invention, which receives and transmits signalling messages to manage subscriber mobility, is characterized in that the network element comprises reception means for receiving the trace command which indicates the tracer and identifies at least one subscriber to be traced whose signalling messages are to be traced, separation means for separating the signalling messages of the subscriber to be traced from other signalling messages, copying means for copying the signalling messages of the subscriber to be traced and transmission means for sending copies to the tracer.

The invention is based on the idea that the network element or process is informed of the subscriber whose messages are to be monitored. After this the network or process automatically carries out monitoring and copies only messages related to this subscriber and sends copies to the desired address where the tracer is. The most important advantage of the invention is that all desired signalling messages can be obtained regardless of the lapse between the messages or whether the messages are sent during a snap shot; not even a single desired message is missed nor is it necessary to search for messages from a large group of irrelevant messages. Furthermore, it is easy to find messages related to one another because they need not be searched from a large group of messages. Usually messages related to one another are successive, and thus it is easy to find them; after all, the messages are sent to the tracer in reception and transmission order. Yet another advantage of the invention is that sending the trace command leads to immediate starting of the tracing. Therefore the fault is discovered as quickly as possible.

In a preferred embodiment of the invention the desired type of the message is also indicated, e.g. messages related to a mobile-terminating call. This has the advantage that the desired messages can be defined more accurately, which makes it even easier to search for the cause of the fault.

In a preferred embodiment of the invention tracing is performed one dialogue at a time. In this case it is advantageous that the messages are obtained as a whole, and thus we do not need to guess what the preceding messages contain.

In a preferred embodiment of the invention copying of messages is not finished until a specific stop command has been received. This has the advantage that the tracer may finish tracing immediately after it has received sufficiently many messages for finding out the fault. If a certain number of messages were always copied, this could lead to copying of too many or too few messages, depending on the case.

Preferred embodiments of the method, system and network element of the invention are disclosed in the appended dependent claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be described in greater detail by means of preferred embodiments with reference to the accompanying drawings, in which

Figure 1 illustrates a mobile communication system,

Figure 2 illustrates an MAP protocol stack,

Figure 3 illustrates signalling according to the invention,

Figure 4 is a flow chart of the function according to a first preferred
5 embodiment of the invention, and

Figure 5 is a block diagram of the element according to the first
preferred embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is applicable to any mobile communication
10 system which supports mobility, such as the third generation mobile
communication systems that are under development, e.g. UMTS (Universal
Mobile Telecommunication System) and IMT-2000 (International Mobile
Telecommunication 2000). In the following the invention is described in greater
detail by examples in connection with the GSM system, but the invention is
15 not, however, limited to this particular system.

Figure 1 is a simplified block diagram of the GSM system. In the
figure all functional elements of the GSM system are located in network
elements which have the same names. Functional elements may also be
integrated, i.e. placed in the same network element. In that case a functional
20 element is often called a process. At least a mobile switching centre MSC,
visitor location register VLR and home location register HLR are in charge of
subscriber services. These are the central functional entities in respect of
mobility management, controlling and signalling. They are responsible for
roaming, for example. This is a characteristic of the mobile communication
25 network which enables correct call routing when the mobile subscriber roams
from one network or cell to another. For example, roaming guarantees that a
call is not interrupted when the mobile user drives from the area of the cell of
one base station to the area of another base station. As regards a more
detailed description of the GSM system, reference is made to *The GSM*
30 *System for Mobile Communications*, M. Mouly and M. Pautet, Palaiseau,
France 1992, ISBN:2-9507190-07-7.

Referring to Figure 1, the network of the GSM system comprises a
base station subsystem BSS and a network subsystem NSS. A mobile station
MS is connected to the base station system BSS via a radio path, the base
35 station system being connected to a mobile switching centre MSC. The mobile

switching centre is responsible for switching calls in which at least one mobile station MS is involved. The mobile switching centre MSC is in contact with other mobile switching centres. Some mobile switching centres MSC are connected to other telecommunications networks ON, such as other public land-based mobile networks PLMN or the public switched telephone network PSTN, and they comprise interconnecting functions for switching calls to and from the networks. The most essential difference between the mobile switching centre MSC and the exchange of a fixed network is that the mobile switching centre also has to perform functions characteristic of mobile communication systems only. For example, the mobile switching centre has to consider the influence of radio resource allocation and manage subscriber mobility together with the network registers. Consequently, the mobile switching centre has to carry out certain procedures, such as procedures related to location registration and changeover.

Two types of databases, i.e. registers, are related to call routing. Information on all subscribers in the network is stored permanently or semi-permanently in the home location register HLR, including information on the services the subscriber has access to and the subscriber's current location. The subscriber information comprises e.g. a subscriber identifier, i.e. IMSI (International Mobile Subscriber Identity), and the subscriber's telephone number MSISDN. One IMSI may have several telephone numbers.

The visitor location register VLR is usually connected to one mobile switching centre MSC, but it may also serve several centres. The visitor location register VLR can be integrated into the mobile switching centre MSC. Such an integrated network element is called a visited mobile switching centre MSC/VLR. When the mobile station MS is active (i.e. it has registered with the network and can make or receive a call), most of the subscriber information related to the mobile station MS and included in the home location register HLR is loaded (copied) into the visitor location register VLR of the mobile switching centre MSC in the area of which the mobile station MS is. The information the VLR has on the mobile station includes the IMSI, MSISDN and location area in which the mobile station is registered, and parameters of supplementary services. The VLR needs this information to process calls which terminate to or originate from the mobile station included in its registers.

The quality of services provided by the network is monitored in a network management subsystem NMS, or to be more precise, in an operation

and maintenance centre OMC located in the NMS. From the operation and maintenance centre OMC the network operator can monitor the function of the network elements and change different network parameters. Operation and maintenance units OMU located in the network elements function as interfaces
5 between the network element and the operator. There is a man machine interface MMI between the operation and maintenance centre and the OMU unit. The operator can give local or remote-controlled commands to the network elements through this interface. The operation and maintenance centre may also comprise smaller operation and maintenance centres, one of
10 them being the main operation and maintenance centre.

In addition to prior art monitoring means, the mobile communication system implementing the functionality of the present invention also comprises means for tracing signalling messages, i.e. means for receiving a trace command, means for detecting the messages to be traced from a group of
15 messages, means for copying the message to be traced and means for sending a copy to the tracer. Implementation of these means does not require changes to the equipment because the existing network elements comprise processors and memory which the functions of the invention can employ. All changes needed to implement the invention can be carried out by adding or
20 updating software routines in the network elements which comprise functions according to the invention.

The mobile communication system uses a mobile application part MAP for transmitting mobile network specific information between the different entities of the same mobile communication network and between the entities
25 in different mobile communication networks. The MAP protocol is a general name for protocols between the functional elements, and MAP protocols are usually processed as a single protocol. The different network elements or processes must support the MAP protocol to exchange the necessary information so that mobile services can be transmitted. If the functional
30 elements are integrated into the same network element, they must use the MAP protocol for external communication, and thus they also preferably use the MAP protocol in their internal communication. In their internal data transmission the functional elements can alternatively use another protocol which is, however, used for performing the functions the mobile application
35 part MAP requires.

An MAP protocol stack according to the GSM system is illustrated in Figure 2. The MAP protocol consists of a number of services the provider of the MAP service, i.e. an MAP entity, offers to the users of MAP services. The users of the MAP service interact with the MAP entity by transmitting or receiving MAP service primitives at the service interface. The MAP service is used by applications which are run above the MAP protocol, such as call control CC, supplementary service SS, mobility management MM and radio resource control RR. In the GSM system all MAP protocols use the services of a TCAP protocol (Transaction Capabilities Application Part) of signalling system SS7, and the TCAP protocol uses services of the SCCP protocol (Signalling Connection Control Part) of SS7. All these protocols use signalling transfer which is provided by the MTP protocol (Message Transfer Part) of the lowest layer. In other mobile communication systems the MAP protocols may use protocols of other signalling systems than SS7.

Figure 3 illustrates signalling according to the first preferred embodiment of the invention. If in the example illustrated in Figure 3 the signalling between A and B occurs in the same network element, it is signalling between processes, i.e. functional elements. If A and B are located in different network elements, signalling occurs between network elements. In both cases network elements receive and transmit messages. A received message means a message received in the signalling between two network elements, and a transmitted message means a message transmitted from a network element. If internal signalling of a network element is involved, in the first preferred embodiment one of the processes is chosen as the process whose received and transmitted messages are monitored. In another embodiment both processes can be monitored. In the example of Figure 3, A denotes a single network element or process, whereas B represents all networks or processes A has a dialogue with. A may be e.g. an MSC which has a dialogue with the VLR and the HLR. B represents these other parties of the dialogue in Figure 3.

Referring to Figure 3, the operation and maintenance centre OMC gives either a local or a remote-controlled trace command to A in signalling message 3-1 (Trace). The signalling message comprises at least the information required for identifying the subscriber, such as the mobile subscriber identifier IMSI or the subscriber's telephone number MSISDN. It is also possible to use other subscriber identifiers, such as a temporary identifier

TMSI. If signalling messages of several subscribers are to be traced, the signalling message 3-1 may include separate identification data of each subscriber or only e.g. the first three digits of the telephone number, in which case signalling messages of each subscriber whose telephone number begins correspondingly are traced. The signalling message 3-1 also indicates the tracer. Depending on the embodiment, the signalling message either always includes the tracer's address or the fact that the address is missing indicates that a default tracer is used or the tracer is the sender of the send command. The tracer may be an element in the operation and maintenance centre OMC, and traced messages are sent to the address of this element. The tracer's address may also be a record in the memory of the network element, from which the information is loaded e.g. into the OMC centre or into a computer at the network element using a separate command. The tracer is by no means connected with the element which gives the trace command, although usually the element that gives the trace command also functions as the tracer. The signalling message 3-1 may also contain information on the desired message type, e.g. signalling related to a call terminating to the subscriber's mobile station.

After A has received message 3-1, it writes down the subscriber, the tracer and the possible message type in its monitoring table. A monitoring table is described in greater detail in connection with Figure 5. Then A starts to monitor the messages it has received and transmitted in a manner to be explained more closely in connection with Figure 4. When it detects a message 3-2 to be traced, it copies it and sends the copy 3-2' to the tracer, which is the OMC in the example of Figure 3. In the first preferred embodiment of the invention A continues monitoring and copying until it receives a command to stop tracing from the OMC in message 3-3 (StopTrace). The stop command contains all the information A needs in order to know which trace is to be stopped. In the first preferred embodiment of the invention message 3-3 includes the same parameters as message 3-1. If message 3-1 identifies more than one subscriber, tracing can be stopped one subscriber at a time. If several tracers have asked to trace messages related to the same subscriber, tracing is preferably stopped one tracer at a time.

Having received message 3-3, A removes the subscriber or subscribers indicated in the message from the monitoring table and stops tracing of their messages.

In another preferred embodiment of the invention the trace command 3-1 is always valid for the duration of one dialogue. When the dialogue ends, A removes the message from the monitoring table and message 3-3 is not needed.

5 The signalling messages described above in connection with Figure 3 are only exemplary and may contain several different messages for transmitting the same information. The messages may also contain other data and they may be combined freely. Furthermore, the names of the messages may change. In addition, other messages, such as acknowledgement
10 messages of messages 3-1 and 3-3, may be transmitted between these messages.

Figure 4 illustrates function according to the first preferred embodiment of the invention in a network element which has received a trace command related to a certain subscriber and to messages of a certain type,
15 e.g. signalling messages related to a mobile-terminating call. In the first preferred embodiment of the invention tracing of signalling messages starts as a dialogue begins. An MAP dialogue is defined as an alternative between two MAP users so that the task can be completed. If the MAP dialogue is related to a specific subscriber, the subscriber's identification data is usually
20 transmitted in the first MAP message. In some cases, e.g. in signalling of phase 2 related to short messages, the subscriber's identification data is not transmitted until in the second MAP message. In these cases the second message is regarded as the starting message of the dialogue related to the subscriber. Messages of different types can be transmitted during the MAP
25 dialogue. At its shortest the dialogue comprises the first message and its acknowledgement.

Referring to Figure 4, a signalling message is received and transmitted in step 400, and in step 401 it is checked whether the message initiates a dialogue, i.e. whether it includes the subscriber's identification data.

30 The subscriber is identified in the MAP messages using either a subscriber identifier-IMSI or a telephone number MSISDN. If the signalling message includes an identifier, it initiates the dialogue. In that case it is checked in step 402 whether the dialogue is to be traced, i.e. whether the subscriber is included in the monitoring table, which is described in greater detail in
35 connection with Figure 5. If the dialogue is to be traced, it will be added to the list of dialogues to be traced in step 403. Then it is checked in step 404

whether the message is of the desired type. If the message is of the desired type, the signalling message is copied in step 405 and a copy is sent to the tracer in step 406. The tracer's address and possibly the desired message type are obtained from the monitoring table and this information may be
5 copied into the list of dialogues to be traced. Then we proceed to step 407 where the signalling message is forwarded according to the prior art. Forwarding means that a received message is transferred for processing and a message to be transmitted is transmitted to the other party of the dialogue.

If it is detected in step 401 that the message does not include an
10 identifier, it is checked in step 408 whether the message belongs to a dialogue related to the subscriber, i.e. whether it is related to the subscriber. If the message does not belong to a dialogue related to the subscriber, we proceed to step 407 where the message is forwarded. If the dialogue belongs to a dialogue related to the subscriber, we proceed to step 409 where it is checked
15 whether the dialogue is on the list of the dialogues to be traced. If this is not the case, we proceed to step 407 where the message is forwarded. If the dialogue is on the list of dialogues to be traced, it is checked in step 410 whether the message stops the dialogue, i.e. whether it is the last message. If the message is not the last message, we return to step 404 to check whether
20 the message is a desired message. If the message is the last message, we proceed to step 411 where the dialogue is removed from the list of dialogues to be traced, after which we return to step 404. In an embodiment where tracing is carried out during one dialogue only, information is also deleted from the monitoring table in step 411.

25 If it is detected in step 402 that the message is not of the desired type, we proceed to step 407 where the signalling message is forwarded. If several trace requests were related to the same subscriber, the check of step 404 and the following actions are carried out one trace request at a time.

The steps illustrated in Figure 4 are not in absolute chronological
30 order and some of the steps can be performed simultaneously or deviating from the chronological order described. Other functions may also be performed between the steps. Some of the steps, e.g. the check in step 404, can also be omitted. In some embodiments copying can be started in the middle of a dialogue. In that case the dialogue has to be linked with the
35 subscriber differently from what was described above. It is essential that received and transmitted signalling messages are monitored and the message

or messages related to the subscriber are picked from among them and a copy of the message is sent to the tracer.

Figure 5 illustrates a network element NE of the invention, such as a mobile switching centre, home location register or visitor location register according to the GSM system. The network element comprises terminals ET for receiving messages from and transmitting messages to other network nodes, an application part AP, which controls the network element, memory M and operation and maintenance unit OMU for receiving commands and instructions from the operator and for answering them. The network element receives the trace command, among other things, via the operation and maintenance unit.

The application part AP comprises different protocol entities, such as an MAP entity ME which transmits MAP services. The MAP entity ME transmits all MAP services of the network element, i.e. all MAP signalling messages are transmitted under the control of the MAP entity. In the first preferred embodiment of the invention the MAP entity carries out the procedures related to tracing in the network element. These procedures were described in greater detail in connection with Figures 3 and 4. In another embodiment these procedures may be carried out by another entity, e.g. an entity of the lower protocol layers or an application entity to be run above the MAP. Procedures may also be divided between different entities. When tracing is carried out at the MAP level, i.e. the MAP entity is responsible for that, the implementation is simpler because at the MAP level information processing is related to the subscriber. A further advantage is that tracing signalling described in Figure 3 may be regarded as part of the MAP protocol.

In the first preferred embodiment the memory of the network element comprises a monitoring table MT, which preferably contains information on the subscribers whose signalling messages are to be traced and information on the tracer, i.e. the address to which copied messages are sent. The monitoring table may also include information on the type of the messages to be traced. If this information is not available, it is assumed that all messages related to the subscriber are to be traced. The information of the monitoring table can be maintained by the OMU or by the MAP entity ME or by both of them. When the network element receives a trace command, the unit maintaining the monitoring table adds the necessary information to the table. If it is told in the trace command that several subscribers should be traced so

that each subscriber is identified separately, the data on each subscriber are added to the monitoring table as if the data were received in separate trace commands. If the trace command identifies a number of subscribers as a single group, e.g. as a group consisting of subscribers having a telephone number beginning with a certain sequence of digits, the data are added as if only one subscriber were involved. Two tracers may be related to the same subscriber, and thus the desired messages may be of the same type or completely different. For example, one of the trace commands related to the same subscriber at the same time may be a command according to which signalling messages related to a mobile-terminating short message are to be sent to the mechanic by to the network element via the operation and maintenance unit OMU. In the other trace command all signalling messages related to the subscriber are copied into the memory of the network element. The information is stored in the monitoring table so that the right tracer receives copies of the correct messages related to the right subscriber or subscribers. In the embodiments where tracing is stopped in response to a stop command, the maintenance unit deletes the subscribers indicated in the stop command as well as information on them from the monitoring table. In the embodiments where tracing is performed one dialogue at a time the information related to the subscriber to be traced is deleted from the monitoring table after the dialogue has ended.

In the first preferred embodiment of the invention a dialogue list (not shown) mentioned in connection with Figure 4 is also stored in the memory M, i.e. a list on the dialogues to be traced which is used for monitoring on-going dialogues. This list is preferably maintained by the MAP entity ME. If the command to stop tracing is received in the middle of an on-going dialogue, the dialogue is not monitored till its end in the first preferred embodiment of the invention, but the dialogue related to the subscriber is deleted from the dialogue list because of the stop trace command. In another embodiment copying and sending of copied messages are not stopped until the dialogue that was possibly going on when the stop command was received ends.

The saving format of information described above is only an example. In other embodiments it is possible to use different data structures and ways of storing information. It is essential that information is available on the subscriber to be traced and the tracer.

It is to be understood that the above description and the figures related to it are only intended to illustrate the present invention. It will be obvious to a person skilled in the art that the invention may be modified in different ways without deviating from the scope and spirit of the invention

5 disclosed in the appended claims.

0976292-01401
T04T29 22629/60

CLAIMS

1. A method of tracing signalling messages of a subscriber in a mobile communication system which comprises functional entities for subscriber mobility management, the method comprising

5 transmitting and receiving signalling messages in a functional entity, **characterized by**

receiving a trace command (3-1) in said functional entity, the command indicating the tracer and identifying at least one subscriber whose signalling messages are to be traced,

10 starting tracing which comprises the steps of:

copying a signalling message in response to the reception or transmission (405) of a signalling message related to the subscriber to be traced, and

sending a copy to the tracer (460, 3-2').

15 2. A method according to claim 1, **characterized** in that the trace command also indicates the type of the signalling message to be traced, and

the signalling message is copied only if it is of the type (404) to be traced.

20 3. A method according to claim 1 or 2, **characterized** in that tracing starts from the start message (401) of a dialogue related to the subscriber to be traced.

4. A method according to claim 3, **characterized** in that tracing of the subscriber's signalling message stops in response to the fact that the dialogue which started tracing ends.

25 5. A method according to claim 1, 2 or 3, **characterized** by receiving a stop command (3-3) of tracing in the entity, the command indicating the subscriber whose signalling message tracing is to be stopped, and

30 stopping tracing of the signalling messages related to said subscriber.

6. A method according to any one of the preceding claims, **characterized** in that the signalling messages of the MAP protocol are traced.

35 7. A mobile communication system comprising

subscribers (MS), at least some of the subscribers being able to roam within the coverage area of the system,

one or more network elements (MSC, VLR, HLR) in which signalling messages are received and transmitted to manage subscriber mobility,

5 operating means (OMC) for giving instructions to the network element,

characterized in that

the operating means (OMC) are arranged to give a trace command to the network element (MSC, VLR, HLR), the command indicating the tracer
10 and identifying at least one subscriber (MS) whose signalling messages are to be traced,

the network element (MSC, VLR, HLR) is arranged to copy signalling messages related to the subscriber (MS) in response to the trace command and to send a copy to the tracer.

15 8. A system according to claim 7, **characterized** in that the trace command also indicates the type of the signalling message to be traced, and

the network element (MSC, VLR, HLR) is arranged to copy the signalling message related to the subscriber to be traced if it is of the type to
20 be traced.

9. A system according to claim 7 or 8, **characterized** in that the signalling messages to be traced are messages of the MAP protocol, and

the network element (MSC, VLR, HLR) is arranged to start copying
25 of the signalling messages related to the subscriber in response to the dialogue of the MAP protocol which starts after the trace command and is related to the subscriber to be traced.

30 10. A network element (NE) of a mobile communication system which receives and transmits signalling messages to manage subscriber mobility, **characterized** in that the network element comprises

reception means (OMU) for receiving a trace command, which indicates the tracer and identifies at least one subscriber whose signalling messages are to be traced,

35 separation means (ME) for separating the signalling messages of the subscriber to be traced from other signalling messages,

copying means (ME) for copying the signalling messages related to the subscriber to be traced, and

transmission means (ME, OMU) for sending copies to the tracer.

11. A network element according to claim 10, **characterized**
5 in that

the trace command also indicates the type of the dialogue to be traced, and

the separation means (ME) are arranged to separate the signalling messages that belong to the dialogue of the type to be traced from the
10 signalling messages of the subscriber to be traced.

12. A network element according to claim 10 or 11, **characterized** in that the network element (NE) comprises an MAP entity (ME) which is responsive to the reception means and comprises separation, copying and transmission means.

204429-22629260

1/2




FIG.1




FIG.2






FIG.3



FOR UTILITY/DESIGN
CIP/PCT NATIONAL/PLANT
ORIGINAL/SUBSTITUTE/SUPPLEMENTAL
DECLARATIONS

RULE 63 (37 C.F.R. 1.63)
DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION

PM & S
FORM

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the INVENTION ENTITLED
TRACING OF SIGNALLING MESSAGES

the specification of which (CHECK applicable BOX(ES))

X A. ☐ is attached hereto.

BOX(ES) è B. ☐ was filed on

as U.S. Application No.

→ C. x was filed as PCT International Application No. PCT/ FI99/00676 on 16 August 1999

and (if applicable to U.S. or PCT application) was amended on

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose all information known to me to be material to patentability as defined in 37 C.F.R. 1.56. Except as noted below, I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International Application which designated at least one other country than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT International Application, filed by me or my assignee disclosing the subject matter claimed in this application and having a filing date (1) before that of the application on which priority is claimed, or (2) if no priority claimed, before the filing date of this application.

PRIOR FOREIGN APPLICATION(S)

Number	Country	Day/MONTH/Year Filed	Date first Laid-open or Published	Date Patented or Granted	Priority NOT Claimed
981773 ✓	FI	18 August 1998 ✓			

If more prior foreign applications, X box at bottom and continue on attached page.

Except as noted below, I hereby claim domestic priority benefit under 35 U.S.C. 119(e) or 120 and/or 365(c) of the indicated United States applications listed below and PCT international applications listed above or below and, if this is a continuation-in-part (CIP) application, insofar as the subject matter disclosed and claimed in this application is in addition to that disclosed in such prior applications, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in 37 C.F.R. 1.56 which became available between the filing date of each such prior application and the national or PCT international filing date of this application.

PRIOR U.S. PROVISIONAL, NONPROVISIONAL AND/OR PCT APPLICATION(S)

Application No. (series code/serial no.)	Day/MONTH/Year Filed	Status	Priority NOT Claimed
		pending, abandoned, patented	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

And I hereby appoint Pillsbury Winthrop LLP, Intellectual Property Group, 1100 New York Avenue, N.W., Ninth Floor, East Tower, Washington, D.C. 20005-3918, telephone number (202) 861-3000 (to whom all communications are to be directed), and the below-named persons (of the same address) individually and collectively my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and with the resulting patent, and I hereby authorize them to delete names/numbers below of persons no longer with their firm and to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/ organization who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct the above firm and/or a below attorney in writing to the contrary.

Paul N. Kokulis	16773	Paul E. White, Jr.	32011	Stephen C. Glazier	31361	William P. Atkins	38821
Raymond F. Lippitt	17519	Glenn J. Perry	28458	Ruth N. Morduch	31044	Paul L. Sharer	36004
G. Lloyd Knight	17698	Kendrew H. Colton	30368	Richard H. Zaitlen	27248	Robin L. Teskin	35030
Kevin E. Joyce	20508	G. Paul Edgell	24238	Roger R. Wise	31204		
George M. Sirilla	18221	Lynn E. Eccleston	35861	Michael R. Dzwonczyk	36787		
Donald J. Bird	25323	Timothy J. Klima	34852	W. Patrick Bengtsson	32456		
Peter W. Gowdey	25872	David A. Jakopin	32995	Jack S. Barufka	37087		
Dale S. Lazar	28872	Mark G. Paulson	30793	Adam R. Hess	41835		

(1) INVENTOR'S SIGNATURE:

Date: 29.1.2001

(1) INVENTOR'S SIGNATURE: <u>Kari Einamo</u>		Date: 29.1.2001	
First	Middle Initial	Family Name	
Residence	<u>Espoo</u>	<u>Finland</u> <u>FI</u>	
City	<u>Finland</u>	<u>Finland</u>	
Mailing Address	<u>Komentajankatu 8 H 61, FIN-02600 Espoo, Finland</u>		
(include Zip Code)			

(2) INVENTOR'S SIGNATURE:

Date:

(2) INVENTOR'S SIGNATURE:		Date:	
First	Middle Initial	Family Name	
Residence			
City	<u>State/Foreign Country</u>	<u>Country of Citizenship</u>	
Mailing Address			
(include Zip Code)			

"X" box ☐ FOR ADDITIONAL INVENTORS, and proceed on the attached page to list each additional inventor.
☐ See additional foreign priorities on attached page (incorporated herein by reference).

Atty. Dkt. No. PM